



# END-GRAIN SEALING WAX

**PROTECTS END-GRAIN WOOD AND CROSSCUT SECTIONS  
FROM CRACKING, SPLITTING AND ABSORPTION OF HUMIDITY  
FOR ALL OUTDOOR WOOD  
WOODEN DECKINGS, SIDINGS, POSTS AND BEAMS etc.**

## PRODUCT CHARACTERISTICS:

SAICOS END-GRAIN SEALING WAX prevents end-grain and crosscuts to absorb humidity, thereby minimizing cracking, checking, splitting, raising grain and bleeding of outdoor decking boards and sidings. - The wood is better protected against discoloration, mildew, warping and twisting, since end-grain wood absorbs water approx. 20 times more than flat-grain wood. SAICOS END-GRAIN SEALING WAX is environmentally friendly and 99 % biodegradable. It is a sealing coat and cannot be overpainted with other finishes.

## COLOUR:

**8131** colourless.

## FIELD OF APPLICATION:

All end-grain, crosscut and notch sections on decks and sidings and other outdoor wood.

## APPLICATION:

The end-cut wood surface must be clean, dry and free from grease, dirt or dust.

Stir can well before use.

If thickened by cold temperatures, warm container slightly up in warm water.

Apply a thin film of SAICOS END-GRAIN SEALING WAX with brush (pure bristles), cloth or sponge.

Will be touch-dry after approx. 1 h. and completely dry after approx. 24 hrs (depending on wood species and air humidity).

## CLEANING OF WORKING UTENSILS:

with SAICOS BRUSH CLEANER (disaromatized white spirit = low odour).

## BEST TEMPERATURE FOR APPLICATION:

between 8° C und 35° C.

Apply on frostfree wood only.

## INGREDIENTS:

Based on natural vegetable oils and waxes in isoparaffin. Does not contain aromatic hydrocarbons, linseed oil or citric terpenes.

Suitable for kindergartens, hospitals and retirement homes.

## PHYSICAL PROPERTIES:

Specific gravity: 0,85 g/cm<sup>3</sup>.

Viscosity: thixotropic, creamy, wax-like.

Odour: mild/weak, odourless when dry (after natural vegetable wax).

Flashpoint: over 61° C according to DIN 53213 (EU Norm-identification not required).

## SAFETY ADVICE:

Keep out of the reach of children. Do not fill into containers normally used for food and drink. Do not bring into contact with victuals and animal food. In case of contact with eyes rinse immediately with plenty of water and seek medical advice. Do not apply in the presence of naked flames.

Wash out any used cloth immediately or store in airtight container (danger of combustion). Dried coat normally inflammable (EURO-Norm EN 13501 - DIN 4102).

## STORAGE PROPERTIES:

At least 5 years if stored in closed container.

Frost resistant.

If thickened by cold temperatures, store at room temperature for some hours to regain normal consistency and stir up well.

## CAN SIZE:

0,125 L

## HEALTH AND ENVIRONMENT:

SAICOS END-GRAIN SEALING WAX does not contain biocides nor preservatives and does not release any physiologically dangerous compounds to the environment.

It is low in odour and odourless when dry.

The above information is given to the best of our knowledge but without liability.

All SAICOS products are made in Germany.

## SAICOS COLOUR GmbH

Carl-Zeiss-Str. 3 · D-48336 Sassenberg · phone +49 (0) 25 83 30 37-0

fax +49 (0) 25 83 30 37-10 · email [info@saicos.de](mailto:info@saicos.de) · [www.saicos.de](http://www.saicos.de)